INFINITE 4 MOTOR WS

79101W







SIDE GUARD With 220 mm height above mattress surface (maximum mattress thickness 100 mm), the safety side guards provide protection for patient from the risk of falling. Care giver can operate the side guards by just one hand. The Infinite side guards were designed to avoid entrapment.

SPECIFICATIONS



MATTRESS PLATFORM The Infinite mattress platform is made of lightweight material and can easily be removed and installed for maintenance and cleaning purpose.



AUTO REGRESSION With Auto Regression feature, the back-raise platform will move 140 mm backwards and 35 mm upwards when the backrest is raised. That way it gives more space in the patient's pelvic area, hence reduces pressure in the abdomen.



WEIGHING SCALE

For patients that has limited mobility, this feature allows the care giver to measure the patients' weight without getting them off the bed.



NURSE CONTROL The nurse control is designed for easy operation for the care giver with lock feature that limits certain bed functions that can be adjusted by patient. With an extra-long cable of 3.5 m, the nurse control can support the care giver flexibly.

DIMENSIONS (mm) ±

1975	
	900



1125 780

InterstationInterstationInterstationInterstationInterstationInterstationInterstationPolypropylene panels (Blow molding process).Positions- Back-raise inclination O - 70°, With Auto regress, approx. 140mm - Knee-raise inclination O - 24°. - Mattress platform elevation 400 (Lo) - 745 (Hi)mm, with bed extension. - Trendelenburg - anti trendelenburg - 14° - 14° - CPR - Electric single touch button. - Auto contour.Battery Backup (approx.)1 hour of use (depending on usage), 6 hours of charging.Castor5" Central lock double wheel castor.IV. PoleStainless steel sections - adjustable. Can be located in four different locations. - X-ray HolderOptionalBack-raise mattress board for x-ray function.CoatingEpoxy powder coating.Max. Patient Weight185 kg.Safe Working Load250 kg.Net Weight (approx.)144 kg.		
Positions- Back-raise inclination O - 70°. With Auto regress, approx. 140mm - Knee-raise inclination O - 24°. - Mattress platform elevation 400 (Lo) - 745 (Hi)mm, with bed extension. - Trendelenburg - anti trendelenburg - 14° - 14° - CPR - Electric single touch button. - Auto contour.Battery Backup (approx.)1 hour of use (depending on usage), 6 hours of charging.Castor5° Central lock double wheel castor.IV. PoleStainless steel sections - adjustable. Can be located in four different locations. - Angle Indicator - X-ray HolderOptionalBack-raise mattress board for x-ray function.CoatingEpoxy powder coating.Max. Patient Weight Safe Working Load185 kg.Safe Working Load250 kg.Dimension (approx.)(L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension).	Construction	
 Knee-raise inclination 0 - 24°. Mattress platform elevation 400 (Lo) - 745 (Hi)mm, with bed extension. Trendelenburg - anti trendelenburg -14° - 14° CPR - Electric single touch button. Auto contour. Battery Backup (approx.) hour of use (depending on usage), 6 hours of charging. Castor 5° Central lock double wheel castor. IV. Pole Stainless steel sections - adjustable. Can be located in four different locations. Accessories Weighing Scale - Accessories Railing Angle Indicator - X-ray Holder Optional Back-raise mattress board for x-ray function. Coating Epoxy powder coating. Max. Patient Weight 185 kg. Safe Working Load 250 kg. Net Weight (approx.) (L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension). 	Head & Foot End Panel	Polypropylene panels (Blow molding process).
Castor 5" Central lock double wheel castor. I.V. Pole Stainless steel sections - adjustable. Can be located in four different locations. Accessories - Weighing Scale - Accessories Railing - Angle Indicator - X-ray Holder Optional Back-raise mattress board for x-ray function. Coating Epoxy powder coating. Max. Patient Weight 185 kg. Safe Working Load 250 kg. Net Weight (approx.) 144 kg. Dimension (approx.) (L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension).	Positions	 Knee-raise inclination 0 - 24°. Mattress platform elevation 400 (Lo) - 745 (Hi)mm, with bed extension. Trendelenburg - anti trendelenburg -14° - 14° CPR - Electric single touch button.
I.V. Pole Stainless steel sections - adjustable. Can be located in four different locations. Accessories - Weighing Scale - Accessories Railing - Angle Indicator - X-ray Holder Optional Back-raise mattress board for x-ray function. Coating Epoxy powder coating. Max. Patient Weight 185 kg. Safe Working Load 250 kg. Net Weight (approx.) 144 kg. Dimension (approx.) (L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension).	Battery Backup (approx.)	1 hour of use (depending on usage), 6 hours of charging.
Accessories - Weighing Scale - Angle Indicator - Accessories Railing - X-ray Holder Optional Back-raise mattress board for x-ray function. Coating Epoxy powder coating. Max. Patient Weight 185 kg. Safe Working Load 250 kg. Net Weight (approx.) 144 kg. Dimension (approx.) (L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension).	Castor	5" Central lock double wheel castor.
- Angle Indicator - X-ray Holder Optional Back-raise mattress board for x-ray function. Coating Epoxy powder coating. Max. Patient Weight 185 kg. Safe Working Load 250 kg. Net Weight (approx.) 144 kg. Dimension (approx.) (L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension).	I.V. Pole	Stainless steel sections - adjustable. Can be located in four different locations.
Coating Epoxy powder coating. Max. Patient Weight 185 kg. Safe Working Load 250 kg. Net Weight (approx.) 144 kg. Dimension (approx.) (L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension).	Accessories	- Weighing Scale - Angle Indicator - Accessories Railing - X-ray Holder
Max. Patient Weight 185 kg. Safe Working Load 250 kg. Net Weight (approx.) 144 kg. Dimension (approx.) (L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension).	Optional	Back-raise mattress board for x-ray function.
Safe Working Load 250 kg. Net Weight (approx.) 144 kg. Dimension (approx.) (L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension).	Coating	Epoxy powder coating.
Net Weight (approx.) 144 kg. Dimension (approx.) (L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension).	Max. Patient Weight	185 kg.
Dimension (approx.) (L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension).	Safe Working Load	250 kg.
	Net Weight (approx.)	144 kg.
	Dimension (approx.)	(L) 2220 x (W) 1075 x (H) 780 - 1125 mm (overall without bed extension). (L) 1975 x (W) 900 x (H) 400 - 745 mm (on mattress platform).

Product images are for illustrative purposes only and color may differ from the actual Specifications subject to change without prior notice

Eff. Date 19-01-2023



MDSS GmbH EC REP Schiffgraben 41 30175 Hannover, Germany



Marketing Office :

Gran Rubina Business Park Lt. 22C. Komp. Rasuna Epicentrum, Jl. HR Rasuna Said - Jakarta 12940 Ph. +62-21-837 00 555. Fax. +62-21-837 00 355, Email: mak@cbn.net.id/marketing@mak-techno.com www.mak-techno.com